

Simply Sew Modern Stitch Along with Quilters Select

Technique Featured:

- Hour Glass (HG) Units, a.k.a. Quarter Square Triangles (QST)
- This creates over-sized QSTs and will be trimmed down

Pro-Tips:

- Read through all instructions before beginning.
- Cut sizes are listed with length of grain x width of ٠ grain.
- Seam Allowance= 1/4"
- rst = right sides together

Hour Glass / Quarter Square Triangle

Dark Fabric (5):

10" square

Accent Fabric (6):


Cut (1)


Cut (1)

10" square

Pro-Tip: For the fastest and most accurate cutting, use a 10" x 10" ruler.

- Draw two diagonal lines corner to corner on the wrong side of each fabric (5) and (6) forming an Х.
- Place the squares rst and stitch ¼" away, on both sides of ONE drawn line.







Page 1 of 4

Pattern design and layout powered by





- Cut on the drawn line between the two lines of stitching creating two HSTs.
- Press each to the dark side.
- Place the two HSTs rst being careful to place the opposite colors on top of each other & align the seams. Stitch ¼" on each side of the drawn line


Pro-Tip: Before stitching across the seam, next the center seams together. This results in the most accurate center match.

- Cut on the drawn line between the two lines of stitching.
- Press seams to the dark side.
- Trim to 8 ½ inches square being careful to keep the intersection in the center.
- Makes two oversized QSTs. Once is needed for the center, reserve the other for another project.

Hint: Wouldn't that extra QST be cute on the back!







Trim to 8 ½"



Page 2 of 4







OPTIONAL CENTER BLOCK

The technique shown below uses a stitch and trim (also known as the stitch and flip) method for more precise units & lends itself well to working with directional fabrics and fussy cutting.

Square in Square – the stitch and flip

method – makes one

Dark Fabric (5): Cut (1)


8 ½" x 8 ½" Square


Accent Fabric (6):

Cut (1) Strip 4 1/2"x WOF, subcut into (4) 4 $\frac{1}{2}$ " squares

- On the back of each 4 ½" square draw a diagonal line corner to corner.
- Place a small square on each of two opposing corners of Fabric (5) square. Marked line positioned as shown & RST.
- Sew <u>on</u> the line. Fold the fabric on the sewn line and press. There will be three layers of fabric at the corner.

Pro-Tip: Ensure proper placement and sewing by checking that the raw edges of all three layers of fabric align into a neat stack.







Page 3 of 4


Design


Pattern design and layout powered by



• Once satisfied with the alignment, trim the back two layers and flip the triangle back into place & press before proceeding

- Place the remaining Fabric (6) square RST in remaining Fabric (5) corners as shown.
- Follow the direction above for sewing, trimming and pressing to construct the remaining triangle corners.





Unit measures 8 1/2" square



Page 4 of 4



Pattern design and layout powered by